



Backhoe Dozer Attachment



High Dumping @ 13.12Ft
Tallest Loader in India



Construction Slits



Material handling at Batching plant



Radial Loader Attachment



BULL DOZER V2

BULL MACHINES PVT. LTD.,

Trichy Road, COIMBATORE - 641 103, INDIA
Ph. : 0422 - 658 6677, 658 6655, Fax : 0422 - 2270955, Cell : 098422 87770
email : sales@bullmachine.com, website : www.bullindia.com

North Zone Office :

H-101, SECTOR - 63, NOIDA - 201 301
Tel : 0120 - 3256 574, 4751 333, Telefax : 2427 165
Mobile : 093120 89285, email : dro@bullmachine.com



Dealer:

RIDING INTO THE FUTURE

www.bullindia.com

FRONT END LOADER ATTACHMENT

V2 11 IMPROVEMENTS

Salient Features of Loader

- Heavy Duty Loader
- 3 - D positional valve mechanism for enhanced operator comfort.
- Bucket level indicator for superior loader application.
- Loader detachable within 20 minutes by a single person at site.
- BQRSL Mechanism : Enables exchanging of loader bucket attachments within seconds by operating a single lever, no spanner required.
- Low diesel Consumption
- Option of various heights dump loaders with : 2.7 m, 3.0m , 4.0m dump heights.

EXTRA
COMFORT
STRENGTH
RELIABILITY
BUCKET OPTIONS



LOADER SPECIFICATION

TECHNICAL DATA	STD. V2 LOADER (mm (ft. inch))	EX. HT. V2 LOADER (mm (ft. inch))	MAX. V2 LOADER (mm (ft. inch))
D Piv height / LR height	2260 (11ft)	2780 (12ft - 1.6 in)	3700 (12ft - 1.6 in)
R Load over height	3100 (10ft - 2 in)	3620 (11ft - 6.5 in)	4050 (14ft - 3.2 in)
M Ditch height @ 45°	2900 (9ft - 9.5 in)	2980 (9ft - 9.8 in)	2880 (9ft - 6 in)
with radial loader/loader (dump height)	-	-	4190 (13ft - 9.12 in)
S Reach at full height fully dished	700 (2ft - 3.6 in)	700 (2ft - 3.6 in)	700 (2ft - 3.6 in)
C Working depth	150 (0.5ft)	150 (0.5ft)	150 (0.5ft)
V Dump Angle	60°	60°	60°
U Roll back of ground	60°	60°	60°




BACKHOE LOADER ATTACHMENT

PATENTED DESIGN - PROTECTS YOUR TRACTOR

Salient Features of backhoe

- Heavy duty backhoe with tear out force of 5700 Kgf
- Shortest Cycle Time in the category.
- Excavation output ~ 1400-1800 Cu.ft / hr with 0.21/.23 cum buckets *
- Attachment mounted free of cost at customer's site
- Diesel Consumption in Backhoe usage - 4 litres*
- Nationwide easy availability of spares and service
- Thousands of satisfied corporate customers

* depends upon the soil conditions



39 Types of Interchangeable Buckets with BQRSL Mechanism



Booster Bucket Stone Bucket Fork lift Grabbing Fork